

GE

Energy Connections

Model 576

Current Transformer
Window Size 2.00" x 5.25"

Application

Metering.

Frequency

50-400 Hz.

Insulation Level

600 Volts, 10 kV BIL full wave.

Continuous Thermal Current Rating Factor

1.33 at 30 °C. amb.,
 1.0 at 55 °C. amb.

Terminals are brass studs No. 10-32
 with one flatwasher, lockwasher and
 regular nut.

Approximate weight 3.5 lbs.



REGULATORY AGENCY APPROVALS



Manufactured to meet the requirements of ANSI/IEEE C57.13.
 Classified by U.L. in accordance with IEC 44-1

Model 576



Catalog Number	Current Ratio	ANSI Metering Class at 60 Hz			Secondary Winding Resistance (Ω @ 75 °C)
		BO.1	BO.2	BO.5	
576-102	1,000:5	0.3	0.3	0.6	0.179
576-122	1,200:5	0.3	0.3	0.6	0.215
576-152	1,500:5	0.3	0.3	0.6	0.173
576-162	1,600:5	0.3	0.3	0.6	0.217
576-202	2,000:5	0.3	0.3	0.3	0.272
576-252	2,500:5	0.3	0.3	0.3	0.339
576-302	3,000:5	0.3	0.3	0.3	0.468
*576-402	4,000:5	0.3	0.3	0.3	0.945
**576-502	5,000:5	0.3	0.3	0.3	1.462
**576-602	6,000:5	0.3	0.3	0.3	2.168

* Rating Factor 0.62 at 30°C.

** Rating Factor 0.55 at 30°C.



Model 576



GEGridSolutions.com

Grid-AIS-L4-ITL_Model_576-1335-2017_06-EN. © Copyright 2017. General Electric Company and Instrument Transformers LLC reserve the right to change specifications of described products at any time without notice and without obligation to notify any person of such changes.

Worldwide Contact Center

Web: www.GEGridSolutions.com/contact

Phone: +44 (0) 1785 250 070

USA and Canada: +1 (0) 800 547 8629

Europe, Middle East and Africa: +34 (0) 94 485 88 00

